

Cannon®

JARRAH

Wood Combustion Heater



22sq
HEATING
CAPACITY

UP TO
72%
HEATING
EFFICIENCY

UP TO
0.7g/kg
EMISSIONS

13.7kW
HEAT OUTPUT

3
SPEED FAN
INCLUDED

The Cannon Jarrah Wood Combustion Heater provides modern design, high quality and durable heating systems in the comfort of your own home. Ideally suited to a medium sized living area, with warm convection or fan assisted heat, Cannon Jarrah makes the perfect addition to the family living environment.

High Efficiency up to 72%

Clean Burning up to 0.7g/kg

High Heat Output at 13.7kw

**Solid 6mm Fire Box
with 8mm Steel Baffle Plate**

**Comfortable Radiant Heat with
Stainless Steel Heat Proof Handle**

3 Speed Electric Fan

**Fire Brick Lining With
Steel Brick Retainer**

**Large Ceramic Glass
Viewing Window**

Cannon®


www.cannonappliances.com.au

10
YEAR
WARRANTY
(FIREBOX)

12
MONTHS
FULL PARTS &
LABOUR
WARRANTY

Installation clearance required from combustible materials

Position A – Parallel position



*When installed with an additional 900mm high x 180° stainless steel rear flue shield fitted between the decromesh casing and the active flue, the rear wall clearance can be reduced to 100mm from a combustible wall.

Position B – Corner position





Fig. 1: Universal/default flue kit

Position A – Parallel position



*When installed with an additional 900mm high x 180° stainless steel rear flue shield fitted between the solid casing and the active flue, the rear wall clearance can be reduced to 150mm from a combustible wall.

Position B – Corner position




Fig. 2: Triple Skin Flue Kit



IMPORTANT: Follow use, care and installation instructions. Heater to be installed by a qualified licensed person, in accordance with AS/NZS 2918:2018 and the appropriate requirements of the relevant building code or codes.

Product Specifications - Model No. 80300

Heating Capacity:	22 squares (205 m ²)
Heat Output:	13.7kW
Heating Efficiency:	Up to 72%
Particulate Emissions:	Up to 0.7g/kg
Overall Dimensions:	843mm H x 710mm W x 638mm D (does not include handle)
Fire Box Dimensions:	300-356mm H x 483mm W x 375mm D

Baffle Plate Thickness:	8mm
--------------------------------	-----

Fix Box Thickness:	6mm
---------------------------	-----

Side wall clearance:	400mm or 425mm dependent of flue type being used. Refer to Fig. 1 and 2
-----------------------------	---

Front Clearance:	500mm
-------------------------	-------

Flue Diameter :	<ul style="list-style-type: none"> • Inner flue stainless steel 152mm diameter • 200mm diameter outer flue coated galvanized 180 degree perforated with solid back or solid triple skin flue kit
------------------------	--

Flue Spigot :	<ul style="list-style-type: none"> • Distance from rear of appliance to centre line of flue spigot - 194mm • Distance from rear of top plate to centre line of flue spigot - 219mm • Distance from side of appliance to centre line of flue spigot - 354mm
----------------------	---

Inner Flue :	Must terminate at least 4.6m above the base of heater
---------------------	---

Fan Assist:	3 Speed
--------------------	---------

Handle:	Stainless Steel
----------------	-----------------

Unit Net Weight:	190kg
-------------------------	-------



THE HOME OF PREMIUM BRANDS

AUSTRALIA
1K Marine Parade, Abbotsford VIC 3067
T: 1300 727 421
E: orders@ixl.com.au
W: cannonappliances.com.au



Whilst every effort is made to provide current information at the time this flyer was produced, continuing product improvements mean the enclosed specifications, images and literature may differ from what is actually available.

CANNON is a registered trademark of Alver Pty Ltd in Australia and New Zealand used under licence by IXL Home Pty Ltd.